

## SciLog® SciCon® Sensors

- sensor technology
- pre-calibrated single-use or extended use

The only pre-calibrated, single-use conductivity sensors with a gamma-stable memory device that stores data of all calibration, and sensor specific information.

The SciLog® SciCon® combines temperature sensing capabilities with conductivity sensing capabilities in a compact, disposable, single-use package at a low price point. Each sensor is pre-programmed and barcoded with a unique ID for easy traceability and data documentation when combined with the SciLog® SciDoc software. Factory calibration data is also stored on each sensor's chip for out-of-box, plug and play use. The SciCon® comes in 5 different sizes to fit a variety of tubing sizes: Luer, 3/8" barb, 1/2" barb, 3/4" Tri-Clover and 1" Tri-Clover Ladish.

### Features and Benefits

- Pre-calibrated
- NIST-traceable
- Certified calibration
- Extended-use sensors (optional)
- Gamma-stable
- NaOH stable
- Autoclave stable
- Comprehensive customer support



Note: SciLog® & SciCon® is a registered trademark of Parker Hannifin Corporation.

### The SciCon® fully integrates and optimizes most existing systems involving...

- Aseptic filtration
- Chromatography
- Reverse osmosis
- Ultrapure water
- Bags and manifolds

### SciCon® Range & Accuracy

- High range: 0.1 - 200 mS range (± 0.25 mS Accuracy)
- Low range: 0 - 100 µS range (± 3 µS Accuracy)



## Sensor Specifications

### Sterilizability

- Can be sanitized: IPA 70%, NaOH (0.1N - 1.0N)
- Autoclavable: (1x)
- Gamma stable: 25-45 kGy

### Material, Fluid Contact

- Medical grade polysulfone
- Meets USP Class VI and FDA 21CFR177.1520
- All wetted materials are made of animal-free compounds

### Sensor Type

- 4-Electrode conductivity cell

### Temperature Probe

- Thermistor

### Sensor Microchip

- EPROM
- Stored sensor ID and calibration factor

### Sensor Connector and Cables

- Dust and water proof IP67



### Size, Part Codes and Specifications

Connector Type	Part Code (Packs of 5)	Compatible Tubing Sizes	Max. Flow Rate*	Max. Pressure
Luer	080-599PSX-5	ID 0.03" to 0.31"	1 L / min	60 psi
3/8" Barb	080-594PSX-5	ID 0.31" to 0.38"	8 L / min	60 psi
1/2" Barb	080-595PSX-5	ID 0.50"	17 L / min	60 psi
3/4" Tri-Clover (TC)	080-596PSX-5	Tubing with 3/4" TC	31 L / min	60 psi
1" Tri-Clover 'Ladish'	080-597PSX-5	Tubing with 1" TC Ladish	60 L / min	60 psi

\* Maximum flow rate @ 1 psi

## Monitor Specifications

### Sensitivity Range

- 1 µS/cm to 200 mS/cm
- 0.1 µS/cm resolution

### Operating Mode / Auto Range Display

- Conductivity: 1 µS/cm to 200 mS/cm
- Temperature: 0°C to 50°C

### Analog Outputs

- 4-20 mA outputs
- 18 bit resolution

### Digital Output

- RS-232

### Alarm Outputs

- 4 TTL switches
- User-selectable hi/lo conductivity
- User-selectable hi/lo temperature

### Power Supply

- 115/230 VAC



Description	Part Code
SciCon® Sensor Monitor	080-590 (110V)
	081-590 (220V)
Sensor Cable (Sensor to Monitor) - 6 ft	090-0491
Sensor Cable (Sensor to Monitor)- 12 ft	090-0491-12

Parker domnick hunter has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact our Process Filtration Sales Department for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's Standard conditions of sale.

