

# Product Data Sheet

## High Pressure Adsorption Dryer DHW

### 100-420 bar (Generation -03)

Version: 1.6.0

Author: Tassilo Tappe

Date: 17.09.2019

### Field of application

Adsorption dryers of the DHW series are designed for drying compressed air and nitrogen to pressure dew points of  $-20^{\circ}\text{C}$  to  $-55^{\circ}\text{C}$  (depending on the design) at operating pressures of up to 420 bar.

### Function

For drying the compressed air, i.e. "adsorption", the compressed air flow is led through a vessel filled with desiccant. The desiccant extracts moisture from the compressed air and stores it in its structure until the desiccant is saturated with moisture. The saturated desiccant then has to be regenerated, i.e. the moisture stored in the structure has to be "removed" before the desiccant can be used for drying again.

Continuous operation of an adsorption dryer therefore requires two vessels that are operated alternately. One vessel is used for drying the compressed air (adsorption) and the other vessel for regenerating the desiccant. For the DHW series the change interval between adsorption and regeneration is 10 minutes at nominal conditions. For the DHW series a certain quantity of dried compressed air is drawn off at the dryer outlet (*approx. 5 % of the nominal volume flow rate at nominal conditions*). This amount of compressed air is expanded to atmospheric pressure and is led through the vessel to regenerate the desiccant. The dried, decompressed air is extremely moisture-subsaturated and thus extracts the moisture stored in the desiccant and discharges it to the atmosphere via a silencer (heatless regeneration).




Abb. DHW 37/250 with several Options (2<sup>nd</sup> pre filter, 2<sup>nd</sup> after filter, timer controlled condensate drains, differential pressure gauges, start-up device (Pressure maintaining valve) and dew point measurement)

### Features

The desiccant has a high drying capacity for moisture and a long service life of several years. This ensures permanently low and stable pressure dew points.

The valves and flow paths required for vessel chamber switch-over are completely installed by high pressure pipes and fittings. The necessary pipe cross sections are calculated individual for each dryer.

The main and regeneration valves are controlled via a solenoid valve block consists of 3 pilot-controlled valves which supply the double acting actuators with control air. To secure the main flow at dryer and regeneration air flow are 4 non-return valves (with big cross section made by FST) mounted in the upper pipe work. One or several silencer (depends on dryer size) are used for effective reduction of the expansion noise.


The valves of the DHW series are controlled by means of a type "C1" processor control system with a 2-line clear text display and 3 operating keys. The control system is installed in a plastic housing with IP65 protection. The clear text display is used for direct and easy-to-understand indication of the operating state, errors, runtimes, service messages etc. If a pressure dew point sensor (option H) is connected, the current pressure dew point of the compressed air is also directly shown on the display and provided as a 4-20 mA signal. The pressure dew point measurement (option H) allows for dew-point dependent operation of the dryer. Depending on the load of the dryer, the adsorption cycle may be extended, i.e. the switch-over frequency is adapted to the operating situation. This minimise the regeneration air consumption and thus the energy costs are minimised.

In addition, the control system provides a compressor synchronising contact. It is used for synchronous operation of the dryer and a compressor which additionally reduces the regeneration air consumption. This function can also be used in conjunction with dew point-dependent operation.

If a differential pressure monitoring system with alarm contact is fitted to the prefilter and afterfilter (option), the alarm contacts can be connected to the control system, displayed and processed.

As standard, the dryer is provided with a prefilter (fine filter) which prevents solid and liquid contaminants from entering the dryer. This increases the service life of the dryer. An afterfilter (general purpose filter) is also provided as standard. It is used to prevent desiccant dust from entering the downstream system. The filters are already fitted to the dryer by using high pressure steel pipes and fittings (pipe work in stainless steel on request)

The dryers comply with the requirements of the Pressure Equipment Directive 2014/68/EU, and have the CE marking of this European directive.



# Product Data Sheet

## High Pressure Adsorption Dryer DHW 100-420 bar



Specifications subject to change without notice

Date 17.09.2019

Latest version see [www.fstweb.de](http://www.fstweb.de)

### Basic data

100 bar model	Nominal volume flow <sup>*1</sup>	Min./Max. allowable operating pressure	Min./Max. allowable operating temperature
DHW 5 / 100	70 m <sup>3</sup> /h	30 - 100 bar	+2°C - +60°C
DHW 9 / 100	100 m <sup>3</sup> /h		
DHW 12 / 100	150 m <sup>3</sup> /h		
DHW 24 / 100	275 m <sup>3</sup> /h		
DHW 37 / 100	420 m <sup>3</sup> /h		
DHW 58 / 100	750 m <sup>3</sup> /h		

\*1 - referred to 1 bar(a) and 20°C at 100 bar operating pressure, inlet temperature 35°C and pressure dew point at outlet -40°C

250 bar model	Nominal volume flow <sup>*2</sup>	Min./Max. allowable operating pressure	Min./Max. allowable operating temperature
DHW 5 / 250	115 m <sup>3</sup> /h	30 - 250 bar	+2°C - +60°C
DHW 9 / 250	170 m <sup>3</sup> /h		
DHW 12 / 250	275 m <sup>3</sup> /h		
DHW 24 / 250	490 m <sup>3</sup> /h		
DHW 37 / 250	730 m <sup>3</sup> /h		
DHW 58 / 250	1450 m <sup>3</sup> /h		

\*2 - referred to 1 bar(a) and 20°C at 250 bar operating pressure, inlet temperature 35°C and pressure dew point at outlet -40°C

350 bar model	Nominal volume flow <sup>*3</sup>	Min./Max. allowable operating pressure	Min./Max. allowable operating temperature
DHW 5 / 350	150 m <sup>3</sup> /h	30 - 350 bar	+2°C - +60°C
DHW 9 / 350	235 m <sup>3</sup> /h		
DHW 12 / 350	320 m <sup>3</sup> /h		
DHW 24 / 350	530 m <sup>3</sup> /h		
DHW 37 / 350	860 m <sup>3</sup> /h		
DHW 58 / 350	1750 m <sup>3</sup> /h		

\*3 - referred to 1 bar(a) and 20°C at 350 bar operating pressure, inlet temperature 35°C and pressure dew point at outlet -40°C

420 bar model	Nominal volume flow <sup>*4</sup>	Min./Max. allowable operating pressure	Min./Max. allowable operating temperature
DHW 5 / 420	150 m <sup>3</sup> /h	30 - 420 bar	+2°C - +60°C
DHW 9 / 420	235 m <sup>3</sup> /h		
DHW 12 / 420	275 m <sup>3</sup> /h		
DHW 24 / 420	560 m <sup>3</sup> /h		
DHW 37 / 420	850 m <sup>3</sup> /h		

\*4 - referred to 1 bar(a) and 20°C at 420 bar operating pressure, inlet temperature 35°C and pressure dew point at outlet -40°C

### Purity classes according to ISO 8573-1

Contamination	
Solid particles <sup>*5</sup>	(Class 2)
Water content <sup>*5</sup>	Class 1-3 <sup>*6</sup>
Total oil content <sup>*5</sup>	Class 1 <sup>*7</sup>

\*5 - typical result, on the assumption that the suitable inlet concentrations and operating and marginal conditions are given

\*6 - depending on the design

\*7 - the oil vapour content is not taken into account, it may reduce the purity class

# Product Data Sheet

## High Pressure Adsorption Dryer DHW 100-420 bar



Specifications subject to change without notice

Date 17.09.2019

Latest version see [www.fstweb.de](http://www.fstweb.de)

### Maintenance rules

	Maintenance interval and maintenance activities
All models	<ul style="list-style-type: none"> <li>■ Once a week :                             <ul style="list-style-type: none"> <li>- Check differential pressure on the prefilter and afterfilter (if installed)</li> <li>- Check function of the condensate drain on the prefilter (if installed)</li> </ul> </li> <li>■ Every 12 months :                             <ul style="list-style-type: none"> <li>- Replace filter elements on pre filter and after filter</li> <li>- Check expansion silencer, clean or replace, if required (SP-FSC-B15F-SV)</li> <li>- Calibrate dew point sensor (option H) (interchange principle possible)</li> </ul> </li> <li>■ Every 24 months :                             <ul style="list-style-type: none"> <li>- Replace solenoid valve block (Art.-no.: SP-VVB230/3-WVM07-REX) <b>with 230VAC</b></li> </ul> </li> <li>■ Every 4 years                             <ul style="list-style-type: none"> <li>- Replace desiccant <sup>*8 *9</sup> ( Art. no. SEDAFILL-DHW .. /... )</li> <li>- Replace flow distributors (Art.-no. : SP-PWS32-DHW25-500bar)</li> </ul> </li> </ul>

\*8 – The regular service life of the desiccant is 2 - 3 years, however, it is very much depending on the contamination level of the incoming compressed air and the operating temperature. In order to achieve the specified service life of the desiccant, it is vital to exchange the filter elements as described above.

\*9 – The desiccant must be disposed of according to the European waste code. A possible oil contamination must be taken into account.

### Product specific data

Specification	
Pressure dew points	-25°C / -40°C / -55°C
Electrical connection	230V 50/60 Hz, alternative 115V 50/60Hz or 24V DC
Power consumption	< 50 Watt
Protection Class	IP 65 (Nema 4)
Valve switching power (for each valve)	10 VA

### Materials

Component	
Vessel and screw taps	carbon steel St.35.8, P265GH (optional Stainless steel)
Frame and supports	carbon steel (optional Stainless steel)
Coating	Outside : sand blasted SA2,5 (ISO8501) ; 1-component primer on alkyd resin base ; dry thickness approx 40 µm (e.g. DuPont PercoTop 021, or similar product) 2-component acrylic resin paint ; dry thickness approx 40 µm (e.g. DuPont PercoTop 9600, or similar product)
Stream distributor	Stainless steel 316
Valve block housing	Brass and stainless steel (optional full stainless steel)
Valve seats	Stainless steel (1.4305,1.4401)
Sealing materials	NBR, PEEK, Hostaform C/9.4002
Screws	8.8 steel, zinc-plated
Pipe connection dryer internal	tubes and fittings steel, galvanised (optional Stainless steel 316)
Pipe connection to pre- and afterfilter	tubes and fittings steel, galvanised (optional Stainless steel 316)
Desiccant filling	80% Molecular sieve 4A and 20% Silicagel WS as water resistant bottom layer
Mounted pre filter and after filter	See product data sheets for filter housing and filter elements

# Product Data Sheet

## High Pressure Adsorption Dryer DHW 100-420 bar



Specifications subject to change without notice

Date 17.09.2019

Latest version see [www.fstweb.de](http://www.fstweb.de)

### Connections, dimensions and weight (including pre filter and after filter)

Model	con- nec- tion	Height	Width 100-250 bar incl. pre- & af- ter filter	Width 350-420 bar incl. pre- & af- ter filter	Depth 100-250 bar	Depth 350-420 bar	Weight 100 bar Version	Weight 250 bar Version	Weight 350 bar Version	Weight 420 bar Version
DHW 5	G 1/2	1050 mm	800 mm	900 mm	450 mm	700 mm	105 kg	130 kg	180 kg	185 kg
DHW 9	G 1/2	1280 mm	800 mm	900 mm	450 mm	700 mm	110 kg	140 kg	190 kg	197 kg
DHW 12	G 1/2	1150 mm	800 mm	900 mm	450 mm	700 mm	120 kg	150 kg	210 kg	220 kg
DHW 24	*)	1280 mm	850 mm	900 mm	450 mm	700 mm	145 kg	200 kg	270 kg	280 kg
DHW 37	*)	1320 mm	1000 mm	1000 mm	700 mm	700 mm	180 kg	250 kg	325 kg	345 kg
DHW 58	*)	1620 mm	1000 mm	1000 mm	700 mm	700 mm	255 kg	350 kg	440 kg	

\*) depends on operating conditions (volume flow and pressure), and so from selected filter size : 1/2" or 3/4"

### Classification according to Pressure Equipment Directive 2014/68/EU for group 2 fluids

Model	Volume	Category	Marking	Commissioning inspection*10	Routine inspection*10
DHW 5/100	2,54 Liter	II	CE 0525	NB*11	---
DHW 9/100	3,59 Liter	II	CE 0525	NB*11	---
DHW 12/100	5,25 Liter	II	CE 0525	NB*11	---
DHW 24/100	9,79 Liter	II	CE 0525	NB*11	---
DHW 37/100	14,93 Liter	III	CE 0525	NB*11	NB*11
DHW 58/100	26,50 Liter	III	CE 0525	NB*11	NB*11
DHW 5/250	1,88 Liter	II	CE 0525	NB*11	---
DHW 9/250	2,61 Liter	II	CE 0525	NB*11	---
DHW 12/250	4,20 Liter	III	CE 0525	NB*11	---
DHW 24/250	7,24 Liter	III	CE 0525	NB*11	NB*11
DHW 37/250	10,88 Liter	III	CE 0525	NB*11	NB*11
DHW 58/250	21,14 Liter	IV	CE 0525	NB*11	NB*11
DHW 5/350	1,69 Liter	II	CE 0525	NB*11	---
DHW 9/350	2,35 Liter	II	CE 0525	NB*11	---
DHW 12/350	3,58 Liter	III	CE 0525	NB*11	NB*11
DHW 24/350	5,84 Liter	III	CE 0525	NB*11	NB*11
DHW 37/350	9,38 Liter	IV	CE 0525	NB*11	NB*11
DHW 58/350	18,65 Liter	IV	CE 0525	NB*11	NB*11
DHW 5/420	1,51 Liter	II	CE 0525	NB*11	---
DHW 9/420	2,09 Liter	II	CE 0525	NB*11	---
DHW 12/420	2,88 Liter	III	CE 0525	NB*11	NB*11
DHW 24/420	5,24 Liter	III	CE 0525	NB*11	NB*11
DHW 37/420	8,06 Liter	IV	CE 0525	NB*11	NB*11

\*10 - In Germany defined by the Ordinance on Industrial Safety and Health of September 27th, 2002 (BGBI. I p. 3777) §14 and §15

\*11 - Inspection by Authorised Person (AP) or Notified Body (NB)

### Other Directives

Model	
All models	EMC-Standard (inspection scope for control system, solenoid valves and dew point measurement): <i>Emitted interference acc. :</i> EN 55011:1998 + A1:1999 + A2:2002 (limit value class: B) EN 61000-3-2:2006-04, EN61000-3-3:2008 <i>Interference resistance acc. :</i> EN 61000-6-2:2005 Machinery Directive 2006/42/EC is not applicable.

# Product Data Sheet


## High Pressure Adsorption Dryer DHW 100-420 bar

Specifications subject to change without notice

Date 17.09.2019

Latest version see [www.fstweb.de](http://www.fstweb.de)

### Flow diagram (PID)





# Product Data Sheet

## High Pressure Adsorption Dryer DHW 100-420 bar



Specifications subject to change without notice

Date 17.09.2019

Latest version see [www.fstweb.de](http://www.fstweb.de)

### Notes

# Product Data Sheet

## High Pressure Adsorption Dryer DHW 100-420 bar

### Accessories



The **DA-CM1-230 switch-over control system** enables the control of two redundant compressed air dryers in a compressed air system. The two dryers can be operated alternately while switching-over automatically. All dryers, provided with a «remote start/stop contact» or a «compressor synchronisation contact», can be directly connected to the switch-over control system without the need for any further modifications. The DA-CM1-230 also controls all required shut-off valves (no scope of supply) to open or close the compressed air line to a dryer (e.g. solenoid valves or valves with actuating drive for 230V AC supply voltage). Furthermore, additional input signals can be hooked up to the common alarm message of each dryer. Beside the power supply the DA-CM1-230 provides alarm inputs for condensate drains, differential pressure gauges, etc. for each dryer.



The **GSM Module DA-ETR-107** is an easy to install extension for all dryers with alarm contact. In case of an alarm a SMS message is send to up to 6 different recipients or, if supported by the provider, an email message. Within the message, the dryer type and serial number is transferred, if required.

The programming can be done with a usual mobile phone, protected by the PIN code of the SIM card (no scope of supply) applied to the GSM module. The DA-ETR-107 is operated with 5-32V DC supply voltage. An internal battery ensures operation of up to 120 hours in case of loss of the supply voltage. The GSM module has an integrated antenna while an external antenna can be connected in the case of low signal levels.



The **Start-up device (minimum pressure valve) DA-VPM-...** protects the dryer from overload due to high flow velocities during pressure build-up of the compressed air system. For connection size G ½ to G 2½ spring loaded angle valves are offered (DA-VPM-B../16), providing an opening pressure of 3-5 bar (standard 3.5 bar). For connection size DN80 to DN250 butterfly valves with pneumatic actuator are offered (DA-VPM-F../11), directly operated by the working pressure while opening at 3 bar (full cross-section at 4 bar). Special versions with adjustable opening pressure or working pressures of up to 450 bar are available on request.



**Differential pressure gauges FAD01C with potential free alarm contact** allow to hook up the differential pressure control of the pre- and after-filter to the common alarm message of each dryer. In order to avoid a false error report due to start-up conditions or short-time peaks, an alarm delay can be set in the dryer control unit. The alarm message then will just be generated, if a too high differential pressure was indicated during the entire delay time interval.

... and many more. Please contact us.