



Adsorption Dehumidifier DehuTech DT-250

Dehumidifying capacity
at 20°C / 60%RH


1,1 kg/h

Dry air flow-rate


290 m³/h



- Washable rotor
- No desiccant carry-over
- Stainless steel casing
- Direct driven fans
- Self-control PTC air heater
- Air filters
- Connection of control equipment
- Option: air condenser
- Easy installation and maintenance
- Long lifetime



TECHNICAL DATA




Dehumidifier, type	DT-250
Nominal capacity *	1,1 kg/h
Dry air flow-rate**	290 m ³ /h
Wet air flow-rate **	50 m ³ /h
Total power	1,3 kW
Supply fuse 230VAC	5,65 A
Rotor regeneration ***	E
Weight	14 kg
Max. noise level	52,9 dB(A)

* Valid for 20°C and 60%RH. For other condition the capacity must be recalculated according to diagram - see below.




** Flow related to air density 1.20 kg/m³.

*** E: electric, G: NG, S: steam, W: hot water

CAPACITY DIAGRAM



DIMENSIONS



FILCO, spol. s r.o.
 Dvorská 464/103
 CZ-503 11 Hradec Králové
 Tel: +420 495 436 233
 info@filco.cz
 www.filco.cz



DehuTech AB
 Enhagsslingan 23,
 S-187 40 Täby, Sweden
 Tel.: +46 8792 04 08
 Fax: +46 8792 55 59
 info@dehutech.com
 www.dehutech.com